





TRICOLOUR LED TWIN SECURITY LIGHT WITH PIR SENSOR

The Ranger Tricolour LED twin security light with sensor is a durable outdoor light with a modern design.

This 24W LED light features an adjustable head and PIR sensor that can be wall or ceiling mountable. Making the Ranger the perfect light for entry ways, alfrescos, garages and walkways.





Efficient





Rating



Quick Connect System



Beam Angle



LED **Lamp Life**



Max Lumen Output



Sensor Angle Max 150°



PIR Motion Sensor



Tricolour LED


- 150° sensor detection angle
- Up to 12m detection distance
- Super bright 24W Tricolour LED light
- Adjustable light duration time
- Day to night adjustable
- Made from durable polycarbonate and an aluminium construction
- New quick connect plate for quick and easy installation
- Wall or ceiling mountable


INCLUDES

Main body, wall mount base, sensor and screws

DIMENSIONS















TRICOLOUR LED SECURITY LIGHT WITH PIR SENSOR

FEATURES

- Modern design
- Made from durable polycarbonate and an aluminium construction
- 24W Tricolour LED light
- PIR sensor with adjustable time sensitivity
- Up to 12m sensor detection distance
- 150° sensor detection angle
- IP54 weather resistant
- New quick connect plate for quick and easy installation
- Wall or ceiling mountable
- Low heat output



SPECIFICATIONS

Model name	Ranger
Model number	White - MLXR3452WS Black - MLXR3452MS
Power (wattage)	24W
Voltage	220v – 240v
Frequency	50Hz
Switchable Tricolour lumens	3000k- 2100lm 4000k- 2200lm 5000k- 2200lm
Colour temperature	3000k / 4000k / 5000k
LED light beam angle	120°
Product size (mm)	252 x 170 x 190
Material	Polycarbonate & Aluminium
	1 Oryotarboriato a Marininani
LED Type	COB
LED Type CRI	,
	COB
CRI	COB ≥80
CRI Approximate lamp life	COB ≥80 25,000hrs
CRI Approximate lamp life Weather resistance rating	COB ≥80 25,000hrs IP54
CRI Approximate lamp life Weather resistance rating Operating temp	COB ≥80 25,000hrs IP54 -20°C to +40 °C
CRI Approximate lamp life Weather resistance rating Operating temp Sensor type	COB ≥80 25,000hrs IP54 -20°C to +40 °C PIR passive infrared sensor
CRI Approximate lamp life Weather resistance rating Operating temp Sensor type Sensor detection angle	COB ≥80 25,000hrs IP54 -20°C to +40 °C PIR passive infrared sensor 150°
CRI Approximate lamp life Weather resistance rating Operating temp Sensor type Sensor detection angle Duration time	COB ≥80 25,000hrs IP54 -20°C to +40 °C PIR passive infrared sensor 150° 10±5s to 4±1min, adjustable

INSTALLATION

Installation	By licensed electrician only
Warranty	2 year replacement warranty*

*For further information regarding warranty terms and conditions, please refer to enclosed warranty statement. Warranty is void unless installed by a licensed electrician.

SHIPPING

Packaging size	L193 x H143 x D131
Gross weight	3.6kg
Carton qty	6

AVAILABLE IN WHITE AND BLACK



Model Colour MLXR3452WS White

Barcode 9312375506591



Model Colour MLXR3452MS Black

Barcode 9312375506584

